

PROTOCOL # 920-D

LUGGAGE TAG

Performance Test	Test Method	Samples	Requirement	Rating (Section or exec. Summary which failed items can be referenced)
LABELING				
Labeling/Packaging	F.P. & L. Act (16 CFR 500)	1 Sample	Should be legibly marked with the following information: Distributor's name, trademark or other means of identification of the manufacturer or packer & address (City, State & Zip) Product identification Net quantity of the contents in terms of weight, measure or numerical count (Metric & US Standard) or a combination so as to give accurate information and facilitate value comparison by the consumer	
Leather and Imitation Leather	Visual Check	All Samples	Country of origin (if imported) Must conform to FTC Guides. Only the top grain leather can be labeled "Genuine" or "Top Grain" A disclosure of the percentage of leather fibers & non-leather substances in the composite or bonded leather	
Adult Tracking Label: **If space limitations exist, contact Kohl's Quality Assurance & Product Integrity teams to discuss minimum required information mr.qa.pi@kohls.com	Kohl's Requirement	All	Can be included on packaging when necessary: Kohl's Assigned Factory Number Manufacture Date (Month/Year) UPC #	
PHYSICAL CHARACTERISTICS				
Maximum Length of retractable cable (if applicable)	Actual Use	1	As Claimed/measured (+3%/-0%)	Claim: Actual:
CONSTRUCTION & WORKMANSHIP				
Kohl's Workmanship Review	Visual Check/Actual Use	All	All components shall be provided as claimed and shall not be deformed or fractured. All hardware shall be provided All welds shall be smoothly finished and free from pits and splatter All components shall not contain any burrs or sharp edges (test by touch or sight) Product shall not contain any loose components or unsecured fastening where rigidity is required Filling material shall be free of objectionable matter and contaminants.	
PERFORMANCE				
Tear Strength (Textile) (Upper Surface of Main Shell/Back Shell/Bottom Shell/Major Outer Materials Only)	ASTM D1424	2 Samples	Tier1: Min. 2.0 lbs. Tier 2: 3.0lbs	
Tear Strength (Leather) (Upper Surface of Main Shell/Back Shell/Bottom Shell/Major Outer Materials Only)	ASTM D4705	2 Samples	Tier 1: Min. 3.0 lbs. Tier 1: Min. 5 lbs.	
*Bursting Strength (Knits)	ASTM D3786	2 Samples	Tier 1: Min. 30 lbs. Tier 2: Min. 40 lbs.	
Seam Strength	ASTM D1683	2 Samples	Tier 1: Min. 25 lbs. / in. Tier 2: Min. 35 lbs. / in.	
Snapping / Unsnapping Force	ASTM D4846	2 Samples	Min. 2 lbs/ Max. 8 lbs.	
Snap / Button Attachment	16 CFR 1500	1 Samples	Tier 1: 17lbs for 10 sec. Tier 2: 25lbs for 10 sec.	
Reinforced Stress Points	ASTM D1683	1 Sample	Tier 1: Min. 10 lbs. Tier 2: Min. 15 lbs.	
Cable Pull-Out	EIA 364-38	1 Sample	No physical damage to the cable assembly shall occur when it is subjected to a 40 N axial load for a minimum of 1 minute while clamping one end of the cable plug.	
Function	Actual Use	1 Sample	Shall function as intended. No major visual change, corrosion or staining after 24 hours @ 100 ° F (38 ° C) and 99% R.H.	
*Resistance To Corrosion (Metal Components)	Kohl's TM 31 Visual Check / Actual Use	1 Sample	All designs and features must conform to actual claim	CLAIM:
COLORFASTNESS				
Dry Crocking	AATCC 8/116	1 Sample	Class 4.0 (textile) Class 3.0 (leather/suede/denim/inner lining)	
Wet Crocking	AATCC 8/116	1 Sample	Class 3.0 (textile) Class 2.0 (leather/suede/denim/inner lining)	
Light Fading	AATCC 16 Option 3 10AFU	1 Sample	Class 4.0 (textile), Class 3.0 (leather/suede)	
ANALYTICAL				
*Lead In Scrapable Surface Coating	EPA SW 846 Method# 3050B/3051A /3052 (Mod.) CPSC-CH- E1003-09	1 Sample	≤ 90ppm (0.009% by weight) (CPSIA) ≤ 200 ppm (Not exceeding 0.020% by weight)	
*Lead In Accessible Substrate Material	EPA SW 846 Method# 3050B/3051A/3052 (Mod.) CPSC-CH- E1001-08 and/or CPSC-CH- E1002-08	1 Sample	(CPSIA) Note: All components that could be touched by a person during normal and reasonably foreseeable use are considered to be accessible. Material exempted from testing: Textiles, natural & manufactured fibers and certain other materials as determined by CPSC (16 CFR 1500.91).	
* CA Prop 65	Refer to Protocol 1300	All Samples	All samples shall be reviewed against the requirements of California Proposition 65 to determine if additional testing or labeling is required.	
*Please refer to Kohl's preferred third party labs for individual pricing and sample size				

<i>In addition to this protocol, any products designed for, intended for or appealing to children, requires additional testing per Testing Protocol # 601.</i>			
Protocol Version	Description of Change	Revised by / Date	Approved by / Date
920-A	Initial Release	Joyce Ho Feb 20, 2014	Elizabeth Armstrong March 17, 2015
920-B	Added testing for retractable cable	Elizabeth Armstrong March 21, 2018	Elizabeth Armstrong March 21, 2018
920-C	Added Adult Tracking Label Req	Elizabeth Armstrong June 15, 2020	Elizabeth Armstrong June 15, 2020
920-D	Removed tier 3 from: Tear Strength, Bursting Strength (Knits), Seam Strength, Snap / Button Attachment, Reinforced Stress Points	Elizabeth Armstrong Dec 2021	Elizabeth Armstrong Dec 2021